

Epson LQ-350

DATASHEET



The highly reliable Epson LQ-350 has a mean time between failure of 10,000 operating hours, and is ideal for front and back office applications needing continuous paper or multi-part stationery.

A very economical printer to run, the LQ-350 helps save money with its high ribbon yield of 2.5 million characters and its low power consumption. Using just 1.3W in sleep mode and 23W when powered on, the LQ-350 is qualified by ENERGY STAR for its excellent energy efficiency.

Easy to integrate, the LQ-350 has Parallel, Serial and USB interfaces as standard, and will fit neatly onto desks thanks to its compact design and cable management system.

KEY FEATURES

- **High reliability**
MTBF of 10,000 operating hours
- **Power-efficient**
1.3W on standby, 22W powered on
- **Economical**
Ribbon yield of 2.5m characters
- **Easy integration**
Parallel, Serial and USB interfaces
- **Compact design**
Fits neatly onto desks

PRODUCT SPECIFICATIONS

| | |
|-------------------------------|--|
| TECHNOLOGY | |
| Number of Pins | 24 pins |
| Number of columns | 80 columns |
| Printing Method | Impact dot matrix |
| PRINT | |
| Printing Speed | HighSpeed-Draft: 10 cpi: 347 chars/s, LQ: 10 cpi: 86 chars/s, Draft: 10 cpi: 260 chars/s |
| Carbon Copies | 3 plus one original |
| Printing Resolution | 360 x 180 dpi |
| CONNECTIVITY | |
| Interfaces | Bidirectional parallel, USB 2.0 Type B, RS-232 |
| PAPER / MEDIA HANDLING | |
| Document Feed | Single sheet rear, Continuous paper rear, Paper output rear |
| Paper Formats | Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Roll Paper, Envelopes |
| GENERAL | |
| Energy Use | 22 W |
| Supply Voltage | AC 200 V - 240 V |
| Energy Star | Yes |
| Product dimensions | 348 x 275 x 154 mm (Width x Depth x Height) |
| Product weight | 4,1 kg |
| Temperature | Operation 5° C - 35° C |
| Compatible Operating Systems | Windows 2000, Windows 7, Windows 8, Windows Vista, Windows XP |
| Included Software | Epson Status Monitor |
| Mean Time Between Failures | 10.000 Hours |
| Print Head Life | 400 Million Strokes/Wire |
| Sound Pressure | Operation: 53 dB (A) |
| Memory | 128 kB included |
| Ribbon Yield | 3000000 characters Black Draft, 2500000 characters Black LQ |
| Humidity | Operation 10% - 80% |
| OTHER FEATURES | |
| Emulations | IBM 2390 Plus, ESC/P2 |
| OTHER | |
| Warranty | 24 months Carry in Optional warranty extension available |

LOGISTICS INFORMATION

| | |
|--------------------------|--------------------|
| SKU | C11CC25001 |
| EAN code | 8715946521886 |
| Dimensions Single Carton | 360 x 450 x 230 mm |
| Carton Weight | 4,43 Kg |
| Multiple Order Quantity | 1 Units |
| Country of Origin | Indonesia |
| Pallet Size Euro | 45 Units (5 x 9) |



Epson Deutschland GmbH
Otto-Hahn-Str. 4
D-40670 Meerbusch
Info-Line: 02159 92 79 500
Telefax: +49 (0) 2159/538-3000
www.epson.de

Epson in Österreich
Info-Line: 01 253 49 78 333
www.epson.at
Epson in der Schweiz
Info-Line: 022 592 7923
www.epson.ch

Alle Marken und eingetragenen Warenzeichen sind das Eigentum der Seiko Epson Corporation oder der jeweiligen Rechteinhaber.
Diese Produktinformationen können ohne vorherige Ankündigung geändert werden.

Epson LQ-350

WHAT'S IN THE BOX

- Main unit
- Setup guide
- User manual (CD)
- Driver and utilities (CD)
- Software (CD)
- Warranty document
- Ribbon

SUPPLIES

- SIDM Black Ribbon Cartridge for LQ-350/300/+/-II (C13S015633)
C13S015633

OPTIONAL ACCESSORIES

- Epson SIDM Paper Roll Holder for LX-300+II/1170II, FX-890/A, FX-2190, LQ-690/300+II series
C12C811141

1. Worldwide sales volume, IDC

EPSON®